

Secure, reliable, intelligent, high density, managed switching for your growing business

Growing businesses require cost effective, networking solutions that can scale with ever changing business needs. The Linksys SRW248G4 Switch with WebView brings a whole new level of intelligence and security to the network infrastructure. The 48 10/100 Mbps ports enable you to consolidate your network from several smaller switches/hubs to a single, managed switch. The optional gigabit optical interfaces allow you to expand the network as your business grows.

Network security is a top priority in any size business. Most business data networks, large and small, are unsecure. Unauthorized access to the network and mission critical data is a constant concern. The SRW248G4 is able to secure the network through 802.1X port authentication and MAC-based filtering. 802.1X requires clients to authenticate themselves before the port will pass data.

Businesses are recognizing the benefits of doing Voice over IP (VoIP) and are quickly migrating their voice services to IP based platforms, requiring their local area networks to support both voice and data applications. In unmanaged IP networks, bursty data sessions can disrupt voice packet delivery, causing poor voice quality. With the enhanced QoS and traffic management features in the SRW248G4, voice data can be prioritized, ensuring clear and reliable voice communications.

Enabling the SRW248G4 advanced features further secures the integrity of your network. The WebView interface provides an intuitive, secure management interface enabling you to better utilize the comprehensive feature-set of the switch, resulting in a better optimized, more secure network.

Simplified, web based user management for more intelligent networking

Quad gigabit uplinks for increased bandwidth and redundancy

802.1X port authentication and MAC address filtering brings network security down to the switch port level QoS enables the network to be optimized for your networked applications, including voice, video and data storage

SRW248G4

PRODUCT DATA

BUSINESS SERIES

48-Port 10/100 + 4-Port Gigabit Switch with WebView



Features

- 48 10/100 Switched RJ-45 ports with auto MDI/MDI-X cable detection
- 4 10/100/1000 Switched RJ-45 ports with auto MDI/MDI-X cable detection
- 2 Shared miniGBIC ports for optical or copper interconnection
- · Non-blocking, store-and-forward switching mechanism
- Simplified QoS management enabled by advanced queuing techniques using 802.1p, Diffserv or ToS traffic prioritzation specifications
- Configuration and monitoring from a standard web browser with WebView management
- Secure remote management of the switch via SSH and SSL secure channel network protocols
- 802.10 based VLANs enable segmentation of networks for improved performance and security
- Private VLAN Edge for simplified network isolation for quests connections or autonomous networks
- Automatic configuration of VLANs across multiple switches through **GVRP/GARP**
- 802.1ab(LLDP) and UPnP support
- User/Network port level security via 802.1X authentication and MAC-based filtering

PRODUCT DATA

BUSINESS SERIES

A Division of Cisco Systems, Inc.

48-Port 10/100 + 4-Port **Gigabit Switch with WebView**

Specifications

Model SRW248G4

Ports 48 RJ-45 connectors for 10BASE-T and 100BASE-TX,

4 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T

with 2 shared SFP slots Auto MDI/MDI-X

Autonegotiate/Manual setting

UTP CAT 5 or better for 10BASE-T/100BASE-TX, Cabling Type

UTP CAT 5e or better for 1000BASE-T

LEDs Power, Link/Act, Speed

Performance

Switching Capacity 17.6 Gbps, non-blocking

MAC table size

Number of VLANs 256 VLANs

Management

Web User Interface Built-in Web UI for easy browser-based configuration (HTTP/HTTPS)

SNMP SNMP version 1, 2, 3 with support for traps

RFC1213 MIB-2, RFC2863 Interface MIB, RFC2665 Ether-like MIB, SNMP MIBs

RFC1493 Bridge MIB, RFC2674 Extended Bridge MIB (P-bridge, Q-bridge), RFC2819 RMON MIB (groups 1,2,3,9 only), RFC 2618 RADIUS Client MIB

RMON Embedded Remote Monitoring (RMON) software agent

supports four RMON groups (history, statistics, alarms, and events)

for enhanced traffic management, monitoring, and analysis

Firmware Upgrade Web Browser upgrade (HTTP)

TFTP upgrade

Port Mirroring Traffic on a port can be mirrored to another port for analysis

with a network analyzer or RMON probe

RFC854 Telnet (Menu-driven configuration) Other Management Secure Shell (SSH) and Telnet Management

Telnet client

SSL security for Web UI Switch audit log **DHCP** client **BootP SNTP**

Xmodem upgrade Cable diagnostics

PING Traceroute Syslog

Security

IEEE 802.1X 802.1X - RADIUS Authentication. MD5 Encryption

Access Control ACLs - Drop or rate limit based on: Source and destination MAC-based

Source and destination IP address*

Protocol* ToS/DSCP* Port* VLAN* Ethertype*

Availability

Link Aggregation Link Aggregation using IEEE 802.3ad LACP

Up to 8 ports in up to 8 trunks

Storm Control Broadcast, Multicast, and Unknown Unicast

IEEE 802.1d Spanning Tree, IEEE 802.1s Multiple Spanning Tree, Spanning Tree

IEEE 802.1w Rapid Spanning Tree, Fast Linkover

IGMP (v1/v2) snooping provides for fast client joins and leaves of **IGMP Snooping**

multicast streams and limits bandwidth-intensive video traffic to

only the requestors

- Increased the bandwidth (up to 8x) and added link redundancy with Link Aggregation Control Protocol (LACP)
- Enhanced rate limiting capabilities and storm control, including multicast, broadcast and flood control
- Port mirroring for non-invasive monitoring of switch traffic
- Mini jumbo frame support
- SNMP v1, v2c, v3
- Fully rack-mountable using the included rack-mounting hardware

Linksys

A Division of Cisco Systems, Inc. 121 Theory

Irvine, CA 92617 USA

E-mail: sales@linksys.com

support@linksys.com

Web: http://www.linksys.com

Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our Worldwide Web Site at www.linksys.com.

PRODUCT DATA

BUSINESS SERIES

QoS

Priority levels 4 Hardware queues

Scheduling Priority Queuing and Weighted Round Robin (WRR)

Class of Service Port-based*

802.1p VLAN priority based*

IPv4/v6 IP Precedence/TOS/DSCP based*

TCP/UDP port-based*

Diffserv*

Classification and remarking ACLs*

Rate Limiting Ingress policer

Egress rate control

Standards 802.3 10BASE-T Ethernet, 802.3u 100BASE-TX Fast Ethernet,

802.3ab 1000BASE-T Gigabit Ethernet, 802.3z Gigabit Ethernet, 802.3x Flow Control, 802.3 ad LACP,802.3af PoE, 802.1D STP, 802.1Q/p VLAN, 802.1w Rapid STP, 802.1s Multiple STP,

802.1X Port Access Authentication

Layer 2

VLAN Port-based and 802.1q based VLANs

Private VLAN Edge (PVE) Management VLAN

HOL Blocking Head of line blocking prevention

Mini jumbo frame Supports frames up to 1600 bytes

Dynamic VLAN GVRP* - Dynamic VLAN Registration

Standards 802.3i 10BASE-T Ethernet, 802.3u 100BASE-TX Fast Ethernet, 802.3ab 1000BASE-T Gigabit Ethernet, 802.3z Gigabit Ethernet,

802.3x Flow Control

Environmental

 Dimensions
 16.93" x 1.75" x 13.78"

 W x H x D
 (430 x 45 x 350 mm)

 Unit Weight
 8.60 lb (3.9 kg)

Power Internal switching power

Certification FCC Part15 Class A, CE Class A, UL, cUL, CE mark, CB

Operating Temperature 32 to $104^{\circ}F$ (0 to $40^{\circ}C$) Storage Temperature -4 to $158^{\circ}F$ (-20 to $70^{\circ}C$)

Operating Humidity 10 to 90% Storage Humidity 10 to 95%

Package Contents

- SRW248G4 48-Port 10/100/1000 Gigabit Switch with WebView
- AC Power Cord
- Rack Mounting Kit with Brackets and Hardware
- · CD with User Guide in PDF Format
- Registration Card
- Console Cable

Minimum Requirements

- Web-Based Utility: Web Browser Microsoft Internet Explorer (Version 5.5 or Above)
- Cat5 Ethernet Network Cables
- · Operating System: Windows 2000, XP or Above

Warranty

5 Years



Check the product package and contents for specific features supported. Specifications are subject to change without notice. Linksys is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2006 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.

Model: SRW248G4 6112011A-RR

^{*} Denotes features found only in v1.1 of hardware