LINKSYS'

Control Two Computers from a Single Console



ProConnect® Integrated KVM 2-Port Switch
Model Number: KVM2KIT

Benefits

- Easily Control Two PCs from a Single Keyboard, Mouse, and Monitor
- Toggle between PCs with Quick, Hot Key Combinations
- Convenient, Built-in Cables for a User-Friendly, All-in-One Design
- Save Desktop Space, Energy, and Hardware Costs
- Free Technical Support—24 Hours a Day,
 7 Days a Week, Toll-Free US Calls
- 1-Year Limited Warranty

ProConnect® Series

Integrated KVM 2-Port Switch

Save Desktop Space—Use a Single Monitor, Keyboard, and Mouse for Two PCs

he Linksys ProConnect® Integrated KVM 2-Port Switch lets you take instant command over two PCs—all from a single keyboard, mouse, and monitor! For your convenience, it even comes with built-in cables to meet all your connection needs.

Switch between PCs with a quick, two-key action, or use the automatic scan feature to easily monitor both computers.

The KVM Switch eliminates those pesky, cableswapping duties while saving you desktop space and hardware costs. Because it doesn't use software, the KVM Switch is compatible with all major desktop and notebook computers. It's the perfect choice for the home, office, or anywhere else you work with two PCs at the same time.

Features

- Supports a Screen Resolution of up to 1920 x 1440
- Complete, Plug-and-Play Monitor Support
- Compatible with Virtually All PS/2 Keyboards and Mice
- Caps Lock, Number Lock, and Scroll Lock Settings Automatically Recalled for Each PC
- Hot-Pluggable—Swap out Your Keyboard, Mouse, or Computers at Any Time
- No Software Required

Specifications

Model Number | KVM2KIT

Standards PS/2

Protocol Microsoft PS/2 Protocol

Ports Keyboard: 1 PS/2 female - Console

2 PS/2 male - CPU

Mouse: 1 PS/2 female - Console

2 PS/2 male - CPU

Monitor: 1 HD15 female - Console

2 HD15 male - CPU

LEDs | PC 1, PC 2

Resolution up to 1920 x 1440

Scan Interval 3, 5, 10, or 20 seconds (3 is default)

Environmental

Dimensions 3.125" x 3.0" x 0.875"

(79.4 mm x 76.2 mm x 22.2 mm)

Unit Weight 11.8 oz. (0.33 kg)

Certifications FCC Class B, CE Mark

Operating Temp. $| 32^{\circ}F \text{ to } 122^{\circ}F \text{ (0°C to } 50^{\circ}C \text{)}$

Storage Temp. | -4°F to 140°F (-20°C to 60°C)

Operating Humidity | 0% to 80%, Non-Condensing

Storage Humidity 0% to 80%, Non-Condensing

Package Contents

ProConnect® Integrated KVM 2-Port Switch

- Integrated KVM 2-Port Switch
- One Quick Installation
- One Registration Card

Minimum Requirements

Console

- One VGA, SVGA, or Multisync Monitor Capable of the Highest Resolution You Will Be Using on Either Computer
- One PS/2 Keyboard
- One PS/2 Mouse

Either Computer

- VGA, SVGA, or Multisync Video Card
- One PS/2 Port for the Keyboard
- One PS/2 Port for the Mouse

Linksys

World Headquarters: 17401 Armstrong Ave. Irvine, CA 92614 USA

E-mail: sales@linksys.com

support@linksys.com

Web: http://www.linksys.com

Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our Worldwide Web Site at www.linksys.com.

