



ProConnect® Series

ProConnect® 4-Station CPU Switch

Connect Multiple PCs
with Just One Console



**ProConnect® 4-Station CPU Switch (SVIEW04 ver. 2)
PS/2 CPU Switch Cabling Kit (SVPS06)**

Benefits

- Switch Instantly Among Multiple PCs with the Touch of a Button
- Benefit from Incredible Savings in Equipment, Space, and Power Costs
- Conserves Desktop and Storage Space
- Serves as a Convenient Docking Station for Notebook PCs
- Free Technical Support—24 Hours a Day, 7 Days a Week for North America Only
- 1-Year Limited Warranty

Conserve Desktop Space While Using Multiple PCs

Take control of your PCs with the ProConnect® CPU Switch. Ready to run out of the box, the ProConnect® CPU Switch lets you connect multiple PCs to a single keyboard, monitor, and mouse. Switch between PCs with the press of a key, or use the switch's cycling feature to rotate between each PC's progress automatically at programmed intervals. Got a notebook PC? Plug it into the CPU Switch and control it from your desktop's full-sized keyboard, monitor, and mouse - just like a docking station!

Built to last, the ProConnect® 4-Port CPU Switch virtually eliminates cable swapping, while you save storage space and hundreds of dollars in hardware costs. Your connection can be simple and inexpensive with the Linksys ProConnect® CPU Switch. It's the perfect choice for any Server room, Internet Service Provider, or testing lab where you need to manage multiple PCs efficiently and easily.

Features

- Supports HotKeys and Pushbutton Switching
- Serves as a Convenient Docking Station for Notebook PCs
- Supports Hot-Swapping of Cables
- Cycling Feature Switches Among PCs Automatically
- Fully Expandable - Cascade CPU Switches Together to Support up to 64 PCs
- Runs with Virtually All Software and Operating Systems
- Compatible with Virtually All Standard PS/2, AT/Serial, and Windows Keyboards
- Sturdy Metal Chassis and Quality Connectors
- Free Technical Support-24 Hours a Day, 7 Days a Week for North America Only
- 1-Year Limited Warranty

Specifications

Model Numbers:	SVIEW04 ver. 2
Cabling Kits*:	SVPS06
Scan Intervals:	5, 10, 20, and 40 seconds
Monitors Supported:	VGA, SVGA, and MultiSync with DDC, DDC2, and DDC2B
Maximum Resolution:	1920 x 1440 SVGA
Ports:	Four CPU ports and three Console ports
Buttons:	Four Port Selection buttons and One Auto Scan Button
LEDs:	Online Port, Selected Port

Environmental

Dimensions:	8.8" x 6" x 2" (224mm x 152mm x 52mm)
Unit Weight:	42.3 oz. (1.2 Kg)
Power:	9V DC (1.62w maximum power consumption)
Certifications:	FCC Class B, CE Mark Commercial
Operating Temp:	5°C to 40°C (41°F to 104°F)
Storage Temp:	-10°C to 60°C (14°F to 140°F)
Operating Humidity:	10% to 85%, Non-Condensing
Storage Humidity:	5% to 90%, Non-Condensing

* Cable kits for connecting PCs to the CPU switch are sold by the above model number, separately. If you have any questions about cabling kits, please contact Linksys for assistance.

Package Contents

ProConnect® 4-Station CPU Switch

- One ProConnect® 4-Station CPU Switch
- One AC Power Adapter
- One User Guide and Registration Card

System Requirements

4-Station Console Ports:

- One VGA, SVGA, or Multisync monitor capable of the highest resolution that you will be using on any computer installed
- One PS/2 style mouse
- One PS/2 style keyboard

PC's:

- One VGA, SVGA or Multisync video card
- One 6-pin mini-DIN (PS/2 style) or DB-9 (standard serial) mouse port
- One 6-pin mini-DIN (PS/2 style) keyboard port with a +5V DC on pin 4 and Ground on pin 3 or a 5-pin DIN (AT style) keyboard port with +5V DC on pin 5 and Ground on pin 4.

One Serial to PS2 adapter for computers using Serial Ports

One AT to PS2 adapter for computers using AT Ports

Please contact Linksys if you have any product questions.

Linksys

17401 Armstrong Ave.
Irvine, CA 92614 USA

Sales Information (800) 546-5797

Technical Support (800) 326-7114

(949) 261-1288

(949) 261-8868

World Wide Web* <http://www.linksys.com>

Email sales@linksys.com

support@linksys.com

China

Tech Support (10) 6432 1920

Sales (10) 6432 1923

Fax (10) 6437 6891

Japan

Telephone (03) 5259-5139

Fax (03) 5259-5117

Philippines

Telephone (632) 638 5580

Fax (632) 635 6772

Singapore

Telephone 552-8998

Fax 552-1024

Thailand

Telephone 717-0770

Fax 717-0738

United Kingdom

Tech Support 0870 7393939

Sales 01245 352403

Fax 0870 7393938

*Visit our website for the most current contact information

