

VX2025wm

20.1" WIDESCREEN, LCD DISPLAY

WITH 8MS CLEARMOTIV™
BROADCAST QUALITY

Elegantly styled, fast widescreen.

ViewSonic's 20.1" VX2025wm shatters conventions with its widescreen aspect ratio and fast 8ms video response time. The widescreen ENHANCES PRODUCTIVITY because it lets you work in two applications side by side without toggling. Take a break from the work to play a video game or watch a movie with no blurs or ghosting thanks to ClearMotiv™ video response. DIGITAL AND ANALOG INPUTS let you connect multiple components and the high brightness and contrast ratio display images in crisp, sharp color. INTEGRATED SPEAKERS and VESA® wall mount-compliance helps alleviate desktop clutter. The latest OSD and power lock prevent accidental changes to your monitor settings, while the Kensington security port offers theft deterrence. The VX2025wm is the desktop display that gives you more bang for your buck.



BEAUTY AND PERFORMANCE FOR DEMANDING PROFESSIONALS

- > **ClearMotiv 8ms video response time**
Ultra-fast 8ms video response enables digital HD broadcast-quality full motion video.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Ultra-high brightness and contrast**
300-nit brightness (typ) and 800:1 contrast ratio (typ) for rich, detailed images.
- > **Multimedia enhanced**
Save desk and workspace and enjoy rich, stereo sound with built-in rear stereo speakers.
- > **Stylish slim-bezel design**
The full 20.1" viewable screen in a thin bezel lets you see more without taking up valuable desktop real estate. The high neck and floating head design accentuate the visual experience.
- > **XtremeView® ultra-wide viewing angles extend your view**
Up to 176° viewing angles horizontally and vertically provide enhanced image legibility from all directions.
- > **Full 20.1" viewable with 1680x1050 resolution**
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Amplified Impluse™ technology**
Advanced amplified impulse technology accelerates grayscale transitions for superior video and gaming.
- > **PC and Mac® compatible**
- > **TCO'99 and ENERGY qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic 

the choice of professionals

VX2025wm

20.1" WIDESCREEN LCD DISPLAY WITH 8MS CLEARMOTIV™ BROADCAST QUALITY



| | | |
|-------------------------|--------------------|--|
| LCD | Type | 20.1" Wide Color TFT Active Matrix LCD |
| | Display Area | 17.1" horizontal x 10.7" vertical; 20.1" diagonal |
| | Optimum Resolution | 1680x1050 |
| | Contrast Ratio | 800:1 (typ) |
| | Viewing Angles | 176° horizontal, 176° vertical @ contrast ratio > 10:1 |
| | Response Time | 8ms gray-to-gray (avg.); 16ms white-black-white (typ) |
| | Light Source | Long life, 40,000 hrs. (typ) |
| | Brightness | 300 cd/m2 (typ) |
| | Panel Surface | Anti-glare |
| VIDEO INPUT | Analog/Digital | RGB analog (75 ohms, 0.7 Vp-p); DVI-D (TMDS, 100 ohms) |
| | Frequency | F _H : 30~82kHz, F _V : 50~75Hz |
| | Sync | H/V separated (TTL), composite, sync-on-green |
| COMPATIBILITY | PC | VGA up to 1680x1054 non-interlaced |
| | Mac®* | Power Mac™ G3/G4/G5 up to 1680x1050 |
| CONNECTOR | Analog/Digital | 15-pin mini D-sub and DVI-D |
| | Power | 3-pin AC plug (CEE22) |
| POWER | Voltage | AC 100~240V, 50~60Hz (auto switch) |
| | Consumption | 35W (typ) |
| CONTROLS | Basic | Power, 1, down, up, 2 |
| | OnView® | Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 6500K-default, 5400K, user color - RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu, language, resolution notice, OSD position, OSD timeout, OSD background, memory recall |
| OPERATING | Temperature | 32~104°F (0~40°C) |
| CONDITIONS | Humidity | 10~90% (non-condensing) |
| DIMENSIONS | Physical (mm) | 485mm x 441mm x 201mm (with stand) 485mm x 340mm x 67mm (without stand) |
| (W x H x D) | Physical (in.) | 19.0" x 17.3" x 7.9" (with stand) 19.0" x 13.4" x 2.6" (without stand) |
| WEIGHT | Net | 13.9 lb. (6.3 kg) (with stand) |
| | Gross | 16.8 lb. (7.7 kg) (with stand) |
| REGULATIONS | | UL, cUL, FCC-B, CB, CE, ENERGY STAR, NOM, NEMKO/GS (covers TUV/GS), NEMKO ERGO (covers TUV/ERGO, ISO13406-2 & MPR II), TCO'99, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, Argentina-S, Green Mark, RoHS |
| POWER MANAGEMENT | | Meets TCO'99 and ENERGY standards |
| PACKAGE CONTENTS | | LCD display, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD |
| WARRANTY | | Three-year limited warranty on LCD, parts and labor |



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12723-00B-12/05] VX2025w-1

ViewSonic 

the choice of professionals

For more product information, visit us on the web at ViewSonic.com