



Stay on top of your work.

The very reliable Samsung ML-2250 laser printer.

DigitAll *reliability*

SAMSUNG

High-output, low-hassle.

Whether you are working in a wired or wireless workgroup, the Samsung ML-2250 series of digital printers is the ideal low-cost, high-output printing solution for you. Up and running in just a few clicks, the ML-2250 will handle big jobs in a hurry with an ultra-fast USB 2.0 interface and a print speed of up to 20 pages per minute. Add in the high toner yield and expandable paper capacity and you'll find the Samsung ML-2250 series of stylishly designed printers is built to help you stay on top of your work.

PC WORLD

RELIABILITY RATING ONLY	Printers
Outstanding	Samsung
Good	Brother, Canon, Epson, HP
Fair	Dell, Lexmark, Minolta
Poor	Xerox/Tektronix

"... Samsung stands head and shoulders above its peers as the only company to earn an outstanding reliability rating ..."

Cited from '03 PC World (USA) annual survey results.

"... Samsung are the only laser printers graded A in consumer reliability ..."

Cited from '03 PC Magazine (USA) annual survey results.

**PC
MAGAZINE**

	Readers' Report Card grade	Overall satisfaction*	Satisfaction with reliability*	Units needing repair in the past 12 months*
Significantly better than average				
Average				
Significantly worse than average				
MONOCHROME LASER (NONMULTIFUNCTION)				
Brother (261)	B			
HP (3,340)	B			
Lexmark (271)	D			
Samsung (113)	A			
Xerox/Tektronix (62)	D			





Outstanding performance.

The ML-2250 series gives you the advanced digital performance you need to help your business succeed.

High output at up to 20 pages (A4)/minute

High resolution at 1,200 x 1,200 dpi

High-speed interface with USB 2.0 (standard)

High volume of 250-sheet paper tray plus 50-sheet multi-purpose tray standard, expandable to 550 sheets with optional extra cassette



**Optional
Extra Cassette**

Economical features.

The ML-2250 series is not only competitively priced, it also has built-in features to save you even more money over time.

Standard high toner capacity yields up to 5,000 pages, more than twice as many as some competitors

One-touch toner save to save up to 40% of your toner, further reducing printing costs per page



Toner Save Button

Maximum flexibility.

The ML-2250 series is designed to adapt to your particular network environment and handle your largest printing jobs with ease.

Network-ready for handling the needs of an entire office environment (standard in ML-2251N, ML-2251NP, ML-2252W, optional for ML-2250)

Wireless for a cable-free office (standard in ML-2252W, optional for ML-2250, ML-2251N, ML-2251NP)

PostScript3-enabled for enhanced printing needs (standard in ML-2251NP, optional for ML-2250, ML-2251N, ML-2252W)

Memory standard 16 MB, expandable to an amazing 144 MB

Paper handling expandable to 550 sheets

Simple to use.

The ML-2250 series features quick and easy set-up and maintenance, to save you time and keep your office running efficiently.

Easy installation with only 4 clicks and no need to reboot your PC

Easy reloading of toner and paper (front-out cover and paper tray)

Samsung ML-2250 series facts and figures

MODEL	ML-2250	ML-2251N	ML-2251NP	ML-2252W
PRINT				
Speed*	Up to 20 ppm in A4 (22 ppm in letter)	Up to 20 ppm in A4 (22 ppm in letter)	Up to 20 ppm in A4 (22 ppm in letter)	Up to 20 ppm in A4 (22 ppm in letter)
Resolution	Up to 1,200 x 1,200 dpi effective output	Up to 1,200 x 1,200 dpi effective output	Up to 1,200 x 1,200 dpi effective output	Up to 1,200 x 1,200 dpi effective output
First Print Out Time	10 seconds	10 seconds	10 seconds	10 seconds
CONTROLLER				
Processor	Samsung 166 MHz	Samsung 166 MHz	Samsung 166 MHz	Samsung 166 MHz
Memory	16 MB (Max. 144 MB)	16 MB (Max. 144 MB)	16 MB (Max. 144 MB)	16 MB (Max. 144 MB)
Emulation	PCL6, IBM ProPrinter, EPSON	PCL6, IBM ProPrinter, EPSON	PostScript3, PCL6, IBM ProPrinter, EPSON	PCL6, IBM ProPrinter, EPSON
Interface	USB 2.0, IEEE1284 Parallel	USB 2.0, IEEE1284 Parallel, Ethernet 10/100 Base TX	USB 2.0, IEEE1284 Parallel, Ethernet 10/100 Base TX	USB 2.0, IEEE1284 Parallel, Ethernet 10/100 Base TX + 802.11b Wireless LAN
Fonts	45 Scalable, 1 Bitmap	45 Scalable, 1 Bitmap	45 Scalable, 1 Bitmap	45 Scalable, 1 Bitmap
OS Compatibility	Windows 95/98/Me/NT4.0/2000/XP, Various Linux	Windows 95/98/Me/NT4.0/2000/XP, Various Linux	Windows 95/98/Me/NT4.0/2000/XP, Various Linux	Windows 95/98/Me/NT4.0/2000/XP, Various Linux
	OS including Red Hat, Caldera, Debian, Mandrake, Slackware, SuSE and Turbo Linux	OS including Red Hat, Caldera, Debian, Mandrake, Slackware, SuSE and Turbo Linux	OS including Red Hat, Caldera, Debian, Mandrake, Slackware, SuSE and Turbo Linux, Mac OS 8.6~9.2/10.1~10.3	OS including Red Hat, Caldera, Debian, Mandrake, Slackware, SuSE and Turbo Linux
PAPER HANDLING				
Input Capacity and Types	250-sheet Cassette Tray, 50-sheet Multi Purpose Tray	250-sheet Cassette Tray, 50-sheet Multi Purpose Tray	250-sheet Cassette Tray, 50-sheet Multi Purpose Tray	250-sheet Cassette Tray, 50-sheet Multi Purpose Tray
Output Capacity and Types	150-sheet Face Down, 1-sheet Face Up	150-sheet Face Down, 1-sheet Face Up	150-sheet Face Down, 1-sheet Face Up	150-sheet Face Down, 1-sheet Face Up
Duplex	Manual	Manual	Manual	Manual
Media size	76 x 127 mm (3" x 5") ~ 216 x 356 mm (8.5" x 14")	76 x 127 mm (3" x 5") ~ 216 x 356 mm (8.5" x 14")	76 x 127 mm (3" x 5") ~ 216 x 356 mm (8.5" x 14")	76 x 127 mm (3" x 5") ~ 216 x 356 mm (8.5" x 14")
Special Media	Transparencies, Labels, Post Card, Envelope	Transparencies, Labels, Post Card, Envelope	Transparencies, Labels, Post Card, Envelope	Transparencies, Labels, Post Card, Envelope
GENERAL				
Dimension (W x D x H)	358 x 452 x 278 mm (14.1" x 17.8" x 10.9")	358 x 452 x 278 mm (14.1" x 17.8" x 10.9")	358 x 452 x 278 mm (14.1" x 17.8" x 10.9")	358 x 452 x 278 mm (14.1" x 17.8" x 10.9")
Weight	10 Kg (22 lbs)	10 Kg (22 lbs)	10 Kg (22 lbs)	10 Kg (22 lbs)
Noise Level**	Less than 53 dBA (Printing), Less than 39 dBA (Standby)	Less than 53 dBA (Printing), Less than 39 dBA (Standby)	Less than 53 dBA (Printing), Less than 39 dBA (Standby)	Less than 53 dBA (Printing), Less than 39 dBA (Standby)
CONSUMABLES				
Type	Single Cartridge	Single Cartridge	Single Cartridge	Single Cartridge
Yield	5,000 Pages at ISO 19752 5% coverage	5,000 Pages at ISO 19752 5% coverage	5,000 Pages at ISO 19752 5% coverage	5,000 Pages at ISO 19752 5% coverage
Model Code	ML-2250D5	ML-2250D5	ML-2250D5	ML-2250D5
OPTIONS				
Network	Ethernet 10/100 Base TX (Internal), Ethernet 10/100 Base TX + 802.11b Wireless LAN (Internal)	Ethernet 10/100 Base TX + 802.11b Wireless LAN (Internal)	Ethernet 10/100 Base TX + 802.11b Wireless LAN (Internal)	N/A
Others	250-sheet Cassette Tray, PostScript3 Emulation Memory: 16 MB, 32 MB, 64 MB, 128 MB	250-sheet Cassette Tray, PostScript3 Emulation Memory: 16 MB, 32 MB, 64 MB, 128 MB	250-sheet Cassette Tray Memory: 16 MB, 32 MB, 64 MB, 128 MB	250-sheet Cassette Tray, PostScript3 Emulation Memory: 16 MB, 32 MB, 64 MB, 128 MB

Distributed by

Please visit www.samsungprinter.com to download the latest software version.

*Print speed will be affected by operating system used, computing performance, application software, connecting method, media type, media size and job complexity.

**Sound Pressure Level, ISO7779.

Samsung Digital Printing Division
www.samsungprinter.com

SAMSUNG